National Semiconductor

February 1995

# LM320L, LM79LXXAC Series 3-Terminal Negative Regulators

## General Description

The LM320L/LM79LXXAC series of 3-terminal negative voltage regulators features fixed output voltages of −5V, −12V, and −15V with output current capabilities in excess of 100 mA. These devices were designed using the latest computer techniques for optimizing the packaged IC thermal/electrical performance. The LM79LXXAC series, even when combined with a minimum output compensation capacitor of 0.1 μF, exhibits an excellent transient response, a maximum line regulation of 0.07% $V_O$/V, and a maximum load regulation of 0.01% $V_O$/mA.

The LM320L/LM79LXXAC series also includes, as self-protection circuitry: safe operating area circuitry for output transistor power dissipation limiting, a temperature independent short circuit current limit for peak output current limiting, and a thermal shutdown circuit to prevent excessive junction temperature. Although designed primarily as fixed voltage regulators, these devices may be combined with simple external circuitry for boosted and/or adjustable voltages and currents. The LM79LXXAC series is available in the 3-lead TO-92 package, and SO-8; 8 lead package. The LM320L series is available in the 3-lead TO-92 package.

For output voltage other than −5V, −12V and −15V the LM137L series provides an output voltage range from 1.2V to 47V.

## Features

- Preset output voltage error is less than ±5% overload, line and temperature
- Specified at an output current of 100 mA
- Easily compensated with a small 0.1 μF output capacitor
- Internal short-circuit, thermal and safe operating area protection
- Easily adjustable to higher output voltages
- Maximum line regulation less than 0.07% $V_{OUT}$/V
- Maximum load regulation less than 0.01% $V_{OUT}$/mA

## Typical Applications

**Fixed Output Regulator**




TL/H/7748–1

*Required if the regulator is located far from the power supply filter. A 1 μF aluminum electrolytic may be substituted.

**Required for stability. A 1 μF aluminum electrolytic may be substituted.

**Adjustable Output Regulator**




TL/H/7748–3

$-V_O = -5V - (5V/R1 + I_Q) \bullet R2$,
$5V/R1 > 3\ I_Q$

## Connection Diagrams

**SO-8 Plastic (Narrow Body)**




TL/H/7748–4

**Top View**

**Order Number LM79L05ACM, LM79L12ACM or LM79L15ACM**
**See NS Package Number M08A**

**TO-92 Plastic Package (Z)**




TL/H/7748–2

**Bottom View**

**Order Number LM320LZ-5.0, LM79L05ACZ, LM320LZ-12, LM79L12ACZ, LM320LZ-15 or LM79L15ACZ**
**See NS Package Number Z03A**

 

RRD-B30M115/Printed in U. S. A.

## Absolute Maximum Ratings

**If Military/Aerospace specified devices are required, please contact the National Semiconductor Sales Office/Distributors for availability and specifications.**

| | |
|---|---|
| Input Voltage | |
| $V_O = -5V, -12V, -15V$ | $-35V$ |
| Internal Power Dissipation (Note 1) | Internally Limited |
| Operating Temperature Range | 0°C to +70°C |
| Maximum Junction Temperature | +125°C |
| Storage Temperature Range | −55°C to +150°C |
| Lead Temperature (Soldering, 10 sec.) | 260°C |

## Electrical Characteristics (Note 2) $T_A = 0°C$ to $+70°C$ unless otherwise noted.

| Output Voltage | | | −5V | | | −12V | | | −15V | | | Units |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| Input Voltage (unless otherwise noted) | | | −10V | | | −17V | | | −20V | | | |
| Symbol | Parameter | Conditions | Min | Typ | Max | Min | Typ | Max | Min | Typ | Max | |
| $V_O$ | Output Voltage | $T_j = 25°C$, $I_O = 100$ mA | −5.2 | −5 | −4.8 | −12.5 | −12 | −11.5 | −15.6 | −15 | −14.4 | |
| | | $1 mA \le I_O \le 100$ mA<br>$V_{MIN} \le V_{IN} \le V_{MAX}$ | −5.25<br>$(-20 \le V_{IN} \le -7.5)$ | | −4.75 | −12.6<br>$(-27 \le V_{IN} \le -14.8)$ | | −11.4 | −15.75<br>$(-30 \le V_{IN} \le -18)$ | | −14.25 | V |
| | | $1 mA \le I_O \le 40$ mA<br>$V_{MIN} \le V_{IN} \le V_{MAX}$ | −5.25<br>$(-20 \le V_{IN} \le -7)$ | | −4.75 | −12.6<br>$(-27 \le V_{IN} \le -14.5)$ | | −11.4 | −15.75<br>$(-30 \le V_{IN} \le -17.5)$ | | −14.25 | |
| $\Delta V_O$ | Line Regulation | $T_j = 25°C$, $I_O = 100$ mA<br>$V_{MIN} \le V_{IN} \le V_{MAX}$ | | | 60<br>$(-20 \le V_{IN} \le -7.3)$ | | | 45<br>$(-27 \le V_{IN} \le -14.6)$ | | | 45<br>$(-30 \le V_{IN} \le -17.7)$ | mV<br>V |
| | | $T_j = 25°C$, $I_O = 40$ mA<br>$V_{MIN} \le V_{IN} \le V_{MAX}$ | | | 60<br>$(-20 \le V_{IN} \le -7)$ | | | 45<br>$(-27 \le V_{IN} \le -14.5)$ | | | 45<br>$(-30 \le V_{IN} \le -17.5)$ | mV<br>V |
| $\Delta V_O$ | Load Regulation | $T_j = 25°C$<br>$1 mA \le I_O \le 100$ mA | | | 50 | | | 100 | | | 125 | mV |
| $\Delta V_O$ | Long Term Stability | $I_O = 100$ mA | | 20 | | | 48 | | | 60 | | mV/khrs |
| $I_Q$ | Quiescent Current | $I_O = 100$ mA | | 2 | 6 | | 2 | 6 | | 2 | 6 | mA |
| $\Delta I_Q$ | Quiescent Current Change | $1 mA \le I_O \le 100$ mA | | | 0.3 | | | 0.3 | | | 0.3 | mA |
| | | $1 mA \le I_O \le 40$ mA | | | 0.1 | | | 0.1 | | | 0.1 | |
| | | $I_O = 100$ mA | | | 0.25 | | | 0.25 | | | 0.25 | mA |
| | | $V_{MIN} \le V_{IN} \le V_{MAX}$ | $(-20 \le V_{IN} \le -7.5)$ | | | $(-27 \le V_{IN} \le -14.8)$ | | | $(-30 \le V_{IN} \le -18)$ | | | V |
| $V_n$ | Output Noise Voltage | $T_j = 25°C$, $I_O = 100$ mA<br>$f = 10$ Hz − 10 kHz | | 40 | | | 96 | | | 120 | | μV |
| $\frac{\Delta V_{IN}}{\Delta V_O}$ | Ripple Rejection | $T_j = 25°C$, $I_O = 100$ mA<br>$f = 120$ Hz | 50 | | | 52 | | | 50 | | | dB |
| | Input Voltage Required to Maintain Line Regulation | $T_j = 25°C$, $I_O = 100$ mA | | | −7.3 | | | −14.6 | | | −17.7 | V |
| | | $I_O = 40$ mA | | | −7.0 | | | −14.5 | | | −17.5 | V |

**Note 1:** Thermal resistance of Z package is 60°C/W $\theta_{jc}$, 232°C/W $\theta_{ja}$ at still air, and 88°C/W at 400 ft/min of air. The M package $\theta_{ja}$ is 180°C/W in still air. The maximum junction temperature shall not exceed 125°C on electrical parameters.

**Note 2:** To ensure constant junction temperature, low duty cycle pulse testing is used.

## Typical Performance Characteristics

**Maximum Average Power Dissipation (TO-92)**




**Peak Output Current**




**Short Circuit Output Current**




**Dropout Voltage**




**Ripple Rejection**




**Output Voltage vs. Temperature (Normalized to 1V @ 25°C)**




**Quiescent Current**




**Output Impedance**




TL/H/7748–5

## Typical Applications (Continued)

**± 15V, 100 mA Dual Power Supply**




TL/H/7748–6

## Schematic Diagrams

**−5V**




TL/H/7748–9

**−12V and −15V**




TL/H/7748–10

## Physical Dimensions inches (millimeters)




**S.O. Package (M)**
**Order Number LM79L05ACM, LM79L12ACM or LM79L15ACM**
**NS Package Number M08A**

## Physical Dimensions inches (millimeters) (Continued)




**Molded Offset TO-92 (Z)**
**Order Number LM320LZ-5.0, LM79L05ACZ, LM320LZ-12, LM79L12ACZ, LM320LZ-15 or LM79L15ACZ**
**NS Package Number Z03A**

**LIFE SUPPORT POLICY**

NATIONAL'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF THE PRESIDENT OF NATIONAL SEMICONDUCTOR CORPORATION. As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, and whose failure to perform, when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury to the user.
2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

**National Semiconductor Corporation**
1111 West Bardin Road
Arlington, TX 76017
Tel: 1(800) 272-9959
Fax: 1(800) 737-7018

**National Semiconductor Europe**
Fax: (+49) 0-180-530 85 86
Email: cnjwge@tevm2.nsc.com
Deutsch Tel: (+49) 0-180-530 85 85
English Tel: (+49) 0-180-532 78 32
Français Tel: (+49) 0-180-532 93 58
Italiano Tel: (+49) 0-180-534 16 80

**National Semiconductor Hong Kong Ltd.**
13th Floor, Straight Block,
Ocean Centre, 5 Canton Rd.
Tsimshatsui, Kowloon
Hong Kong
Tel: (852) 2737-1600
Fax: (852) 2736-9960

**National Semiconductor Japan Ltd.**
Tel: 81-043-299-2309
Fax: 81-043-299-2408