

Artikel Nr: 469711 - 469722

Isolierschlauch nach DIN 40621

Material: Weich-PVC
Standardfarbe: transparent
Temperaturbereich: -20°C bis +90°C
Durchschlagsfestigkeit: 1kV/0,1mm Wandstärke

Type	Innen-Ø	Außen-Ø	Stärke
	mm	mm	mm
BG-0,5	0,50	1,30	0,40
BG-1,0	1,00	1,80	0,40
BG-1,5	1,50	2,30	0,40
BG-2,0	2,00	2,80	0,40
BG-2,5	2,50	3,30	0,40
BG-3,0	3,00	3,80	0,40
BG-3,5	3,50	4,30	0,40
BG-4,0	4,00	5,00	0,50
BG-4,5	4,50	5,50	0,50
BG-5,0	5,00	6,20	0,60
BG-5,5	5,50	6,70	0,60
BG-6,0	6,00	7,20	0,60
BG-6,5	6,50	7,70	0,60
BG-7,0	7,00	8,40	0,70
BG-8,0	8,00	9,40	0,70
BG-9,0	9,00	10,40	0,70
BG-10,0	10,00	11,40	0,70
BG-11,0	11,00	12,40	0,70
BG-12,0	12,00	13,60	0,80
BG-13,0	13,00	14,60	0,80
BG-14,0	14,00	16,00	1,00
BG-15,0	15,00	17,00	1,00
BG-16,0	16,00	18,00	1,00
BG-17,0	17,00	19,00	1,00
BG-18,0	18,00	20,00	1,00
BG-20,0	20,00	22,00	1,00
BG-22,0	22,00	24,40	1,20
BG-24,0	24,00	26,40	1,20
BG-25,0	25,00	27,40	1,20
BG-26,0	26,00	28,40	1,20
BG-28,0	28,00	30,40	1,20
BG-30,0	30,00	32,40	1,20

Angaben können je nach
Hersteller schwanken !

