Products
Motherboard Series
»N68PV-GS
»Overview & Specifications
»Download
»Manual
»FAQ
»CPU Support List

Welcome to ASRock Hall 017, D35 CeBIT 1-5 MARCH 2011
P67/H67 B3 Stepping MB is Ready To Go
Statement for Intel 6 Series Chipset Issue
ASRock Channel on YouTube
facebook Follow ASRock on facebook now!
ASRock Forum
FATAL1TY
Absolute Performance P67 / H67 Series
Vision 3D
XFast USB Boosts up your USB speed
SmartView

N68PV-GS



SHARE |



- Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback
- NVIDIA® PureVideo™ Ready
- Gigabit LAN
- Supports Smart BIOS, ASRock OC Tuner (Up to 130% CPU frequency increase & 210% FSB Speed increase)
  - Supports Extra ESD Protection, Intelligent Energy Saver (Up to 15% CPU Power Saving)

This model may not be sold worldwide. Please contact your local dealer for the availability of this model in your region.





Product Specifications

General	
CPU	- Support up to 95W Socket AM2+* / AM2 processors: AMD Phenom™ FX / Phenom / Athlon 64 FX / Athlon 64 X2 Dual-Core / Athlon X2 Dual-Core / Athlon 64 / Sempron processor (For detail CPU support list, please click here) - Supports AMD's Cool 'n' Quiet Technology - FSB 1000 MHz (2.0 GT/s) - Supports Untied Overclocking Technology - Supports Hyper-Transport Technology - AM3 CPU Ready* *If you use AM3 / AM2+ CPU on AM2 chipset motherboard, the system bus speed will downgrade from HT3.0 (5200 MT/s) to HT1.0 (2000 MT/s), but the CPU frequency will not be influenced.
Chipset	- NVIDIA® GeForce 7050 / nForce 630A MCP
Memory	- Dual Channel DDR2 memory technology - 2 x DDR2 DIMM slots - Supports DDR2 1066*/800/667/533 non-ECC, un-buffered memory - Max. capacity of system memory: 8GB** *Support with AM3 / AM2+ CPU. **Due to the operating system limitation, the actual memory size may be less than 4GB for the reservation for system usage under Windows® 32-bit OS. For Windows® 64-bit OS with 64-bit CPU, there is no such limitation.
BIOS	- 4Mb AMI BIOS - AMI Legal BIOS - Supports "Plug and Play" - ACPI 1.1 Compliance Wake Up Events - Supports jumperfree - SMBIOS 2.3.1 Support - Supports Smart BIOS
Audio, Video and Networking	
Graphics	- Integrated NVIDIA® GeForce7 Series (NV44) - DX9.0 VGA, Pixel Shader 3.0 - Max. shared memory 256MB - Dual VGA Output: Support DVI-D and D-Sub ports by independent display controllers - Supports DVI with max. resolution up to 1920x1200 @ 75Hz - Supports D-Sub with max. resolution up to 1920x1440 @ 60Hz - Supports HDCP function with DVI-D port - Supports Full HD 1080p Blu-ray (BD) / HD-DVD playback with DVI-D port - NVIDIA® PureVideo™ Ready
Audio	- 5.1 CH Windows® Vista™ Premium Level HD Audio (ALC662 Audio Codec) - Chipset embedded HDMI Audio
LAN	- Gigabit LAN 10/100/1000 Mb/s - Giga PHY Realtek RTL8211CL - Supports Wake-On-LAN
Expansion / Connectivity	
Slots	- 1 x PCI Express x16 slot - 1 x PCI Express x1 slot - 2 x PCI slots
Connector	- 4 x SATAII 3.0 Gb/s connectors, support RAID (RAID 0, RAID 1, RAID 0+1, RAID 5 and JBOD), NCQ, AHCI and "Hot Plug" functions - 1 x ATA133 IDE connector (supports 2 x IDE devices) - 1 x Floppy connector - 1 x COM port header - 1 x Print port header - CPU/Chassis FAN connector - 24 pin ATX power connector - 4 pin 12V power connector - CD in header - Front panel audio connector - 2 x USB 2.0 headers (support 4 USB 2.0 ports)

Rear Panel I/O	I/O Panel - 1 x PS/2 Mouse Port - 1 x PS/2 Keyboard Port - 1 x VGA/D-Sub Port - 1 x VGA/DVI-D Port - 4 x Ready-to-Use USB 2.0 Ports - 1 x RJ-45 LAN Port with LED (ACT/LINK LED and SPEED LED) - HD Audio Jack: Line in / Front Speaker / Microphone
Other Features / Miscellaneous	
Unique Feature	- ASRock OC Tuner - Intelligent Energy Saver - Instant Boot - Hybrid Booster: - CPU Frequency Stepless Control - ASRock U-COP - Boot Failure Guard (B.F.G.) - ASRock AM2 Boost: ASRock Patented Technology to boost memory performance up to 12.5%
Support CD	- Drivers, Utilities, AntiVirus Software (Trial Version)
Accessories	- Quick Installation Guide, Support CD, I/O Shield - ATA 133 Cables (optional) - 1 x SATA Data Cable (optional) - 1 x SATA 1 to 1 Power Cable (optional)
Hardware Monitor	- CPU Temperature Sensing - Chassis Temperature Sensing - CPU Fan Tachometer - Chassis Fan Tachometer - CPU Quiet Fan - Voltage Monitoring: +12V, +5V, +3.3V, Vcore
Form Factor	- Micro ATX Form Factor: 9.6-in x 7.2-in, 24.4 cm x 18.3 cm
OS	- Microsoft® Windows® 7 / 7 64-bit / Vista™ / Vista™ 64-bit / XP / XP 64-bit / 2000 compliant
Certifications	- FCC, CE, WHQL

Caution:
Please realize that there is a certain risk involved with overclocking, including adjusting the setting in the BIOS or using the third-party overclocking tools. Overclocking may affect your system stability, or even cause damage to the components and devices of your system. It should be done at your own risk and expense. We are not responsible for possible damage caused by overclocking.

The specification is subject to change without notice in advance. The brand and product names are trademarks of their respective companies. Any configuration other than original product specification is not guaranteed.

© 2002-2011 ASRock Inc. All rights reserved. | Information published on ASRock.com is subject to change without notice.